


CAN06C201MAGAC7411

CAN SMD Indust 250, Ceramic, 200 pF, 20%, COG, SMD Chip, MLCC, AC Rated, 0603, 0.5 mm



Click here for the 3D model.

D	imei	nsi	ons

Dimensions		
Chip Size	0603	
L	1.6mm +/-0.15mm	
W	0.8mm +/-0.15mm	
т	0.8mm +/-0.10mm	
S	0.5mm MIN	
В	0.35mm +/-0.15mm	

Packaging Specifications

Packaging Packaging Quantity T&R, 330mm, Paper Tape 15000

General Information				
Series	CAN SMD Indust 250			
Style	SMD Chip			
Description	SMD Chip, MLCC, AC Rated			
Features	Temperature Stable, Class I			
RoHS	Yes			
Termination	Tin			
Marking	No			
AEC-Q200	No			
Typical Component Weight	4.6 mg			
Shelf Life	78 Weeks			
MSL	1			

Specifications	
Capacitance	200 pF
Measurement Condition	1 MHz 1.0Vrms
Tolerance	20%
Voltage AC	250 VAC
Dielectric Withstanding Voltage	945 VDC
Temperature Range	-55/+125°C
Temp. Coefficient	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	15%, 1MegaHz 1.0Vrms
Dissipation Factor	0.1% 1 MHz 1.0Vrms
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	10 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.