


## CAN19C473KAGACTU

Aliases (CAN19C473KAGAC7800) CAN SMD Indust 250, Ceramic, 0.047 uF, 10%, COG, SMD Chip, MLCC, AC Rated, 1825, 2.3 mm



Click	horo	for the	3D	mode
CIICK	nere	TOT THE	90	mode

Dimensions		
Chip Size	1825	
L	4.5mm +/-0.3mm	
W	6.4mm +/-0.4mm	
T	1.4mm +/-0.15mm	
S	2.3mm MIN	
В	0.6mm +/-0.35mm	
5	0.011111 7 0.0011111	

Packaging Specifications				
Packaging	T&R, 180mm, Plastic Tape			
Packaging Quantity	1000			

General Information	
Series	CAN SMD Indust 250
Style	SMD Chip
Description	SMD Chip, MLCC, AC Rated
Features	Temperature Stable, Class I
RoHS	Yes
Termination	Tin
Marking	No
AEC-Q200	No
Typical Component Weight	190 mg
Shelf Life	78 Weeks
MSL	1

Specifications	
Capacitance	0.047 uF
Measurement Condition	1 kHz 1.0Vrms
Tolerance	10%
Voltage AC	250 VAC
Dielectric Withstanding Voltage	945 VDC
Temperature Range	-55/+125°C
Temp. Coefficient	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	15%, 1kHz 1.0Vrms
Dissipation Factor	0.1% 1 kHz 1.0Vrms
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	10 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 07/19/2025 © 2006 - 2025 YAGEO