



Click [here](#) for the 3D model.

#### Dimensions

|   |                 |
|---|-----------------|
| D | 8mm +/-0.5mm    |
| L | 9.7mm +/-0.3mm  |
| W | 0.8 - 1.1mm     |
| F | 0.2mm MAX       |
| A | 8.3mm +/-0.2mm  |
| B | 8.3mm +/-0.2mm  |
| C | 9mm +/-0.2mm    |
| G | 0.35mm +/-0.2mm |
| P | 3.1mm +/-0.2mm  |

#### Packaging Specifications

|                    |            |
|--------------------|------------|
| Packaging          | T&R, 380mm |
| Packaging Quantity | 500        |

#### General Information

|              |                                 |
|--------------|---------------------------------|
| Series       | A767                            |
| Dielectric   | Polymer Aluminum                |
| Style        | SMD Can                         |
| Description  | Surface Mount, Polymer Aluminum |
| RoHS         | Yes                             |
| Lead         | V-Chip                          |
| AEC-Q200     | No                              |
| Halogen Free | true                            |

#### Specifications

|                         |                          |
|-------------------------|--------------------------|
| Capacitance             | 56 uF                    |
| Capacitance Tolerance   | 20%                      |
| Voltage DC              | 35 VDC, 40.2 VDC (Surge) |
| Temperature Range       | -55/+105°C               |
| Rated Temperature       | 105°C                    |
| Life                    | 2000 Hrs                 |
| ESR                     | 31 mOhms (100kHz 20C)    |
| Impedance               | 31 mOhms                 |
| Ripple Current          | 1900 mAmps (100kHz 105C) |
| Leakage Current         | 392 uA (2min 20°C)       |
| High Temperature Solder | true                     |