




ALC80, Aluminum, Aluminum Electrolytic, 27,000 uF, 20%, 40 VDC, –40/ +105°C, 10 mm



Click	horo	for the	3D	model
CIICK	nere	TOT LITE	ദാഗ	mode

Dimensions	
D	40mm +1mm
L	50mm +/-2mm
S	10mm +/-0.1mm
LL	4mm +/-1mm
F	2mm +/-0.1mm
Parks in Constitution	

Packaging Specifications		
Sleeving	Yes	
Packaging	Bulk, Bag	

General Information	
Series	ALC80
Dielectric	Aluminum Electrolytic
Description	Snap-In, Aluminum Electrolytic
RoHS	Yes
Lead	3 Pin Short
AEC-Q200	No
Halogen Free	Yes
Typical Component Weight	105 g
Notes	Dimensions D And L Include Sleeving.
Shelf Life	156 Weeks

Specifications				
Capacitance	27,000 uF			
Tolerance	20%			
Voltage DC	40 VDC, 46 VDC (Surge)			
Temperature Range	-40/+105°C			
Rated Temperature	105°C			
Life	9000 Hrs (Rated Voltage And Ripple Current At 105C), 14000 Hrs (Rated Voltage at 105C)			
ESR	25.7 mOhms (100Hz 20C), 21.91 mOhms (10kHz 20C)			
Ripple Current	9.903 Amps (100Hz 105C), 11.6 Amps (10kHz 105C)			
Leakage Current	3240 uA (5min 20°C)			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 12/04/2025 © 2006 - 2025 YAGEO