




ALH82, Aluminum, Aluminum Electrolytic, 91 uF, 20%, 600 VDC, –40/ +105°C, 10 mm



Packaging





PCB LAYOUT



General Information Series ALH82 Dielectric Aluminum Electrolytic Description Snap-In, Aluminum Electrolytic RoHS Yes AEC-Q200 No Halogen Free Yes Typical Component Weight 45 g Shelf Life 156 Weeks

Click here for the 3D model.

Dimensions	
D	30mm +/-1mm
L	35mm +/-2mm
S	10mm +/-0.1mm
LL	6.3mm +/-1mm
F	2mm +/-0.1mm
Packaging Specifications	

Tray

Specifications	
Capacitance	91 uF
Tolerance	20%
Voltage DC	600 VDC
Temperature Range	-40/+105°C
Rated Temperature	105°C
Life	3000 Hrs (Rated Voltage And Ripple Current At 105C)
ESR	1534 mOhms (100Hz 20C), 1036 mOhms (10kHz 20C)
Ripple Current	1.1 Amps (100Hz 105C), 3.12 Amps (10Hz 105C)
Leakage Current	163 uA (5min 20°C)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and	
we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the	
requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us	
with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained	

Generated 11/03/2025 © 2006 - 2025 YAGEO