


ARRO7D103KWS

ARR Indust X7R HT200C, Ceramic, 0.01 uF, 10%, 100 VDC, X7R, ARR Indust X7R HT200C with C3 Technology, Radial, 5.08mm



Click here for the 3D model.

Dimensions	
L	7.62mm MAX
W	7.62mm MAX
Т	3.81mm MAX
S	5.08mm
LL	31.75mm MIN
F	0.635mm +/-0.051mm

Packaging Specifications			
Packaging	Waffle, Tray		
Packaging Quantity	28		

General Information			
Series	ARR Indust X7R HT200C		
Style	Radial		
Description	ARR Indust X7R HT200C with C3 Technology, Radial		
Features	High Temperature		
RoHS	No		
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.		
SCIP Number	6906e33d-ee54-4964-bee2-22e2ed2d0d24		
Termination	Lead (SnPb)		
Lead	Wire Leads		
AEC-Q200	No		

Specifications	
Capacitance	0.01 uF
Capacitance Tolerance	10%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	250 VDC
Temperature Range	-55/+200°C
Temperature Coefficient	X7R
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	15%, 1kHz 1.0Vrms
Dissipation Factor	2.5%1kHz 1.0Vrms
Aging Rate	2% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.