


## C062C682J1G5CA

Aliases (C062C682J1G5CA)

LDD Comm COG, Ceramic, 6800 pF, 5%, 100 VDC, COG, 5.08mm



Click here for the 3D model.

Dimensions	,
L	7.37mm +/-0.25mm
Н	7.37mm +/-0.25mm
Т	2.29mm +/-0.25mm
S	5.08mm +/-0.38mm
LL	31.75mm MIN
F	0.635mm +0.102/-0.051mm

Packaging Specifications			
Packaging	Bulk, Bag		
Packaging Quantity	100		

General Information		
Series	LDD Comm COG	
Style	Radial	
Features	Commercial	
RoHS	No	
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	8c864fd1-202b-4ce7-85fd-56c9e19121ad	
Termination	Lead (SnPb)	
Lead	Wire Leads	
Failure Rate	N/A	
AEC-Q200	No	

Specifications			
Capacitance	6800 pF		
Capacitance Tolerance	5%		
Voltage DC	100 VDC		
Dielectric Withstanding Voltage	250 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	COG		
Dissipation Factor	0.1% 1 kHz 25C		
Insulation Resistance	147 MOhms		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.