



TOP VIEW

Single or Double Chip Stack



PROFILE VIEW

Single Chip Stack



General Information

|                          |   |
|--------------------------|---|
| Series                   | KPS SMD Comm X8L HT150C                           |
| Style                    | Stacked Chip                                      |
| Description              | SMD, MLCC, Stacked, Single Chip, High Temperature |
| Features                 | High Temperature                                  |
| RoHS                     | Yes   |
| Termination              | Tin   |
| AEC-Q200                 | No  |
| Typical Component Weight | 160 mg  |
| Chip Size                | 1210-1  |
| Shelf Life               | 78 Weeks  |
| MSL                      | 1   |

Specifications

|  |   |
|--|---|
| Capacitance  | 0.47 uF   |
| Measurement Condition  | 1 kHz 1.0Vrms   |
| Capacitance Tolerance  | 10%   |
| Voltage DC   | 50 VDC  |
| Dielectric Withstanding Voltage                                    | 125 VDC   |
| Temperature Range  | -55/+150°C  |
| Temperature Coefficient  | X8L   |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC) | +15% (-55C to +125C), +15/-40% (125C to 150C), 1kHz 1.0Vrms |
| Dissipation Factor   | 2.5% 1 kHz 1.0Vrms  |
| Aging Rate   | 3% Loss/Decade Hour: Referee Time is 1000 Hours             |
| Insulation Resistance  | 1.0638 GOhms  |

Click [here](#) for the 3D model.

Dimensions

|   |                  |
|---|------------------|
| L | 3.5mm +/-0.3mm   |
| W | 2.6mm +/-0.3mm   |
| T | 3.35mm +/-0.10mm |
| B | 0.8mm +/-0.15mm  |

Packaging Specifications

|                    |                          |
|--------------------|--------------------------|
| Packaging          | T&R, 180mm, Plastic Tape |
| Packaging Quantity | 600                      |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.