


C4ASYBU3220A3FJ

Specifications

C4AS, Film, Metallized Polypropylene, Power, 0.22 uF, 5%, 3,000 VDC, 750 VAC, 70°C, 37.5 mm



General Information	
Series	C4AS
Dielectric	Metallized Polypropylene
Style	Radial
RoHS	Yes
Lead	Wire Leads
AEC-Q200	No

Click here for the 3D model.

Dimensions	
L	41.5mm -0.7mm
н	40mm -0.7mm
Т	20mm -0.7mm
S	37.5mm +/-0.4mm
LL	6mm -2mm
F	1.2mm NOM

Bulk, Bag

58

Packaging Specifications

Packaging Packaging Quantity

0.22 uF Capacitance 5% Tolerance Voltage DC 3000 VDC 750 VAC Voltage AC **Temperature Range** -40/+85°C 70°C **Rated Temperature Dissipation Factor** 0.05% Max dV/dt 2,070 V/us 9.4 mOhms (100kHz) ESR **Ripple Current** 14 Amps (100kHz 70C), 455 Amps (Peak)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.