


## C4BSWBX3470ZGFJ

C4BS, Film, Metallized Polypropylene, Power, 0.47 uF, 5%, 2000 VDC, 700 VAC, 70°C, 22mm



Click here for the 3D model.

Dimensions	
L	41.5mm +1.5/-0.7mm
Н	40mm +0.2/-0.7mm
Т	20mm +0.4/-0.7mm
S	22mm +/-0.2mm
S1	4mm +/-0.2mm
Р	10.5mm NOM

Packaging Specifications			
Packaging	Bulk, Bag		
Packaging Quantity	52		

General Information	
Series	C4BS
Dielectric	Metallized Polypropylene
Style	Radial
Features	IGBT Circuit
RoHS	Yes
Lead	Flat Tabs
AEC-Q200	No
Typical Component Weight	51.29 g
Miscellaneous	KEMET Style G Tabs.

Specifications			
Capacitance	0.47 uF		
Capacitance Tolerance	5%		
Voltage DC	2000 VDC		
Voltage AC	700 VAC		
Temperature Range	-40/+85°C		
Rated Temperature	70°C		
Max dV/dt	1379 V/us		
ESR	5.1 mOhms (100kHz)		
Ripple Current	20 Amps (100kHz 70C), 648 Amps (Peak)		
Inductance	41 nH		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.