


CANO6C561MAGACTU

Aliases (CANO6C561MAGAC7867) CAN SMD Indust 250, Ceramic, 560 pF, 20%, COG, SMD Chip, MLCC, AC Rated, 0603, 0.5 mm

CAN SMD Indust 250

SMD Chip, MLCC, AC Rated

SMD Chip



	Features	Temperature Stable, Class I
	RoHS	Yes
	Termination	Tin
S	Marking	No
	AEC-Q200	No
	Typical Component Weight	4.6 mg
	Shelf Life	78 Weeks
Click here for the 3D model.	MSL	1
	Specifications	

General Information

Series

Style

Description

Dimensions	
Chip Size	0603
L	1.6mm +/-0.15mm
W	0.8mm +/-0.15mm
T	0.8mm +/-0.10mm
S	0.5mm MIN
В	0.35mm +/-0.15mm

Packaging Specifications	
Packaging	T&R, 180mm, Paper Tape
Packaging Quantity	4000

Specifications	
Capacitance	560 pF
Measurement Condition	1 MHz 1.0Vrms
Tolerance	20%
Voltage AC	250 VAC
Dielectric Withstanding Voltage	945 VDC
Temperature Range	-55/+125°C
Temp. Coefficient	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	15%, 1MegaHz 1.0Vrms
Dissipation Factor	0.1% 1 MHz 1.0Vrms
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	10 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 07/16/2025 © 2006 - 2025 YAGEO