


## CANO6X161GAGACTU

Aliases (CAN06X161GAGAC7867) CAN SMD Indust 250, Ceramic, 160 pF, 2%, COG, SMD Chip, MLCC, AC Rated, 0603, 0.4 mm



| Click here | for the | 3D model |
|------------|---------|----------|
|------------|---------|----------|

| Dimensions |                  |
|------------|------------------|
| Chip Size  | 0603             |
| L          | 1.6mm +/-0.17mm  |
| W          | 0.8mm +/-0.15mm  |
| T          | 0.8mm +/-0.10mm  |
| S          | 0.4mm MIN        |
| В          | 0.45mm +/-0.15mm |
|            |                  |

| Packaging Specifications |                        |
|--------------------------|------------------------|
| Packaging                | T&R, 180mm, Paper Tape |
| Packaging Quantity       | 4000                   |

| General Information      |                             |
|--------------------------|-----------------------------|
| Series                   | CAN SMD Indust 250          |
| Style                    | SMD Chip                    |
| Description              | SMD Chip, MLCC, AC Rated    |
| Features                 | Temperature Stable, Class I |
| RoHS                     | Yes                         |
| Termination              | Flexible Termination        |
| Marking                  | No                          |
| AEC-Q200                 | No                          |
| Typical Component Weight | 4.6 mg                      |
| Shelf Life               | 78 Weeks                    |
| MSL                      | 1                           |

| Specifications   |                      |
|--|----------------------|
| Capacitance  | 160 pF               |
| Measurement Condition  | 1 MHz 1.0Vrms        |
| Tolerance  | 2%                   |
| Voltage AC   | 250 VAC              |
| Dielectric Withstanding Voltage  | 945 VDC              |
| Temperature Range  | -55/+125°C           |
| Temp. Coefficient  | COG                  |
| Capacitance Change with<br>Reference to +25°C and 0 VDC<br>Applied (TCC) | 15%, 1MegaHz 1.0Vrms |
| Dissipation Factor   | 0.1% 1 MHz 1.0Vrms   |
| Aging Rate   | 0% Loss/Decade Hour  |
| Insulation Resistance  | 10 GOhms             |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 08/02/2025 © 2006 - 2025 YAGEO