


CAN22X124GAGAC

CAN SMD Indust 250, Ceramic, 0.12 uF, 2%, COG, SMD Chip, MLCC, AC Rated, 2225



General Information	
Series	CAN SMD Indust 250
Style	SMD Chip
Description	SMD Chip, MLCC, AC Rated
Features	Temperature Stable, Class I
RoHS	Yes
Termination	Flexible Termination
Marking	No
AEC-Q200	No
Shelf Life	78 Weeks
MSL	1

Specifications Capacitance 0.12 uF 1 kHz 1.0Vrms Measurement Condition Tolerance 2% Voltage AC 250 VAC **Dielectric Withstanding Voltage** 945 VDC **Temperature Range** -55/+125°C Temp. Coefficient COG Capacitance Change with Reference to +25°C and 0 VDC 15%, 1kHz 1.0Vrms Applied (TCC) 0.1% 1 kHz 1.0Vrms **Dissipation Factor** Aging Rate 0% Loss/Decade Hour 8.333 GOhms Insulation Resistance

Click here for the 3D model.

Dimensions	
Chip Size	2225
L	5.9mm +/-0.75mm
W	6.4mm +/-0.4mm
т	2.5mm +/-0.20mm
В	0.7mm +/-0.35mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	1

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.