


CDR35BX104BKZS

Aliases (C1825N104K1XSL, C1825N104K1XSL-MilitaryBulk)

SMD Mil PRF55681, Ceramic, 0.1 uF, 10%, 100 VDC, BX, S (0.001%/1000 Hrs), 1825



Click here for the 3D model.

Dimensions	,
Chip Size	1825
L	4.5mm +/-0.3mm (0.177 in +/-0.012 in)
W	6.4mm +/-0.3mm (0.252 in +/-0.012 in)
Т	1.5mm (0.059 in)
В	0.5mm +/-0.3mm (0.02 in +/-0.012 in)

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	1

General Information	
Series	SMD Mil PRF55681
Style	SMD Chip
RoHS	No
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
Termination	Lead (SnPb)
Failure Rate	S (0.001%/1000 Hrs)
Testing and Reliability	MIL-PRF-55681
Qualifications	MIL-PRF-55681
AEC-Q200	No
Miscellaneous	Termination Description: SolderPlate 70-30.
Shelf Life	78 Weeks
MSL	1

Specifications	
Capacitance	0.1 uF
Capacitance Tolerance	10%
Voltage DC	100 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	BX

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.