


## CT-07-50

## Aliases (USEN075000000)

 $\label{lem:KEMET} KEMET, CT, Current, Round - Toroidal, AC, Overcurrent/Currect \ Detection, High Sensitivity, High Performance$ 



Click here for the 3D model.

Dimensions	
D	5.9mm NOM
L	19mm NOM
Н	20.2mm NOM
Т	10mm MAX
LL	5.5mm +/-0.5mm

Packaging Specifications	
Packaging	Tray
Packaging Quantity	1200
Typical Component Weight	5.4 g

General Information		
Series	СТ	
Type	Current	
Style	Round - Toroidal	
Description	Low Alternating Current Sensor	
Features	Overcurrent/Currect Detection, High Sensitivity, High Performance	
Lead	4 Wire Leads	
RoHS	Yes	
REACH	Yes	
Notes	0.8 mm Diamter Pin Connectors	

Specifications	
Temperature Range	-20/+80°C
Miscellaneous	Materials = Phenolic Resin Case, Epoxy-Filled. 500 turns.

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.