


F463DB123J2K0Z

Obsolete

F463, Film, Metallized Polypropylene, General Purpose, 0.012 uF, 5%, 2,000 VDC, 85°C, 22.5 mm



Click	horo	for th	2D	model.
CIICK	nere	TOL LI	le SD	modei.

General Information	
Series	F463
Dielectric	Metallized Polypropylene
Style	Radial
Features	MKP, Pulse
RoHS	Yes
Termination	Cut (Tinned Wire)
Lead	Cut/Short
AEC-Q200	No
Typical Component Weight	3.561 g
Miscellaneous	The Rated Voltage Decreases 2%/C Between +85C And +105C (1.25%/C For AC). ClimCat: 55/105/56.
Notes	Series Replaced by R75.

Dimensions		
L	26mm -0.5mm	
Н	14.5mm -0.5mm	
Т	6mm -0.5mm	
S	22.5mm +/-0.4mm	
LL	4mm +2mm	
F	0.8mm +/-0.05mm	
G	0.5mm NOM	
Packaging Specifications		

Packaging Specifications	
Packaging	Pizza, Box
Packaging Quantity	660

Specifications	
Capacitance	0.012 uF
Tolerance	5%
Voltage DC	2000 VDC, 1200 VDC (105C)
Voltage AC	700 VAC
Temperature Range	-55/+105°C
Rated Temperature	85°C
Dissipation Factor	0.04% 1kHz, 0.06% 10kHz, 0.25% 100kHz
Insulation Resistance	100 GOhms
Max dV/dt	4,500 V/us
Inductance	6 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 10/16/2025 © 2006 - 2025 YAGEO