


## F862FC105K310ZLH0J

F862, Film, Metallized Polypropylene, Automotive Safety, 1 uF, 10%, 630 VDC, 310 VAC (X2), 110°C, 27.5mm



Click here for the 3D model.

| Dimensions |                 |
|------------|-----------------|
| L          | 31.5mm -0.7mm   |
| Н          | 20mm -0.7mm     |
| Т          | 11mm -0.7mm     |
| S          | 27.5mm +/-0.4mm |
| LL         | 17mm -1mm       |
| F          | 0.8mm +/-0.05mm |
| G          | 0.5mm NOM       |

| Packaging Specifications |            |
|--------------------------|------------|
| Packaging                | Pizza, Box |
| Packaging Quantity       | 300        |

| General Information         |  |
|-----------------------------|--|
| Series                      | F862   |
| Dielectric                  | Metallized Polypropylene   |
| Style                       | Radial   |
| Features                    | MKP EMI, Aumotive Grade, Harsh<br>Environmental Conditions, Heavy Duty |
| RoHS                        | Yes  |
| Lead                        | Wire Leads   |
| Safety Class                | X2   |
| Qualifications              | ENEC, UL, cUL, CQC, AEC-Q200   |
| AEC-Q200                    | Yes  |
| THB Performance             | Yes  |
| Halogen Free                | Yes  |
| Typical Component<br>Weight | 9.133 g  |
| Miscellaneous               | ClimCat: 40/110/56/B.  |
| Shelf Life                  | 104 Weeks  |
|                             |  |

| Specifications        |              |
|-----------------------|--------------|
| Capacitance           | 1uF          |
| Capacitance Tolerance | 10%          |
| Voltage DC            | 630 VDC      |
| Voltage AC            | 310 VAC (X2) |
| Temperature Range     | -40/+110°C   |
| Rated Temperature     | 110°C        |
| Dissipation Factor    | 0.2% 1kHz    |
| Insulation Resistance | 10 GOhms     |
| Max dV/dt             | 150 V/us     |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.