


FLLD3075AMHT5

Aliases (LLD3075AMHT5)

Obsolete

EMI Filters, KEMET, FLLD3-MH, Chassis Mount, Noise Suppression, 240x80x135mm



General Information	
Series	FLLD3-MH
Style	Chassis Mount
Description	EMI Filter, Chassis Mount, Motor Drives
Features	Three Phase, High Performance, High Voltage
Phase	Three-phase
RoHS	Yes
Qualifications	IEC/EN 60939, UL 1283
AEC-Q200	No
Lead	Threaded Studs M6
Terminal Type	Threaded Studs M6

530 VAC, 305 VAC

Click hara for the 3D mod	
	_1

Dimensions	
L	240mm NOM
W	80mm NOM
Н	135mm NOM
L1	255mm NOM
L2	270mm NOM
W1	60mm NOM
J	70mm NOM
K	6.5mm NOM
M (Earth)	Threaded Studs M6
Lead	Threaded Studs M6

80mm NOM	Rated Frequency	50-60 Hz
135mm NOM	Rated Current	75 A (50°C)
255mm NOM	Ripple Current	75 A (50°C)
270mm NOM	Rated Temperature	50°C
60mm NOM	Temperature Range	-25/+100°C
70mm NOM	Climate Category	25/100/21
6.5mm NOM	Test Voltage DC (P to P)	2250 VDC
Threaded Studs M6	Test Voltage DC (P to E)	3000 VDC
Threaded Studs M6	Max Power Loss	30 W (25°C 50 Hz)
	Leakage Current	4.7 mA

Specifications

Voltage AC

Packaging Specifications	
Packaging	Bulk
Packaging Quantity	1
Typical Component Weight	3,200 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 11/27/2025 © 2006 - 2025 YAGEO