


FLLE2032AQDD

Aliases (LLE2032AQDD)

Obsolete

EMI Filters, KEMET, FLLE2-Q, Chassis Mount, Noise Suppression, 800 uH, 91x51x45mm



General Information	
Series	FLLE2-Q
Style	Chassis Mount
Description	Single Phase, Chassis Mount Filters
Features	Single Phase
Phase	Single-phase
RoHS	Yes
Qualifications	IEC/EN 60939, UL, CSA
AEC-Q200	No
Lead	Wire Leads
Terminal Type	Wire
Test Voltage DC (P to N)	1300 VDC

Dimensions	
L	91mm MIN
W	51mm MIN
н	45mm MIN
Lead	Wire Leads
Packaging Specifications	
Packaging	Bulk

415 g

Packaging Quantity

Typical Component Weight

Specifications	
Voltage AC	300 VAC
Voltage DC	300 VDC
Inductance	0.8 mH
Rated Frequency	50-60 Hz
Rated Current	32 A
Ripple Current	32 A
Rated Temperature	40°C
Temperature Range	-25/+100°C
Climate Category	25/100/21
Leakage Current	0.79 mA
Test Voltage DC (P/N to E)	2250 VDC

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute -	- and
we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who hav	ve the
requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by	by us
with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.	•

Generated 07/16/2025 © 2006 - 2025 YAGEO