


LDBCC3100GC5N0

Aliases (DBCC3100GC5N0)

LDB, Film, Metallized PPS Stacked, General Purpose, 0.1 uF, 2%, 50 VDC, 125° C, 2 mm, 1812 / 4532



General Information	
Series	LDB
Dielectric	Metallized PPS Stacked
Style	SMD Chip
RoHS	Yes
AEC-Q200	No
Typical Component Weight	0.267 g
Shelf Life	104 Weeks
MSL	3

Click here for the 3D model.

Dimensions	
L	4.7mm +0.3/-0.2mm
W	3.3mm +/-0.3mm
Т	2mm MAX
В	0.4mm +0.5/-0.3mm
Case Code (EIA / mm)	1812 / 4532

Packaging Specifications	
Packaging	T&R
Packaging Quantity	3000

Specifications		
Capacitance	0.1 uF	
Tolerance	2%	
Voltage DC	50 VDC	
Temperature Range	-55/+125°C	
Rated Temperature	125°C	
Dissipation Factor	0.6% 1kHz	
Insulation Resistance	3 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 12/04/2025 © 2006 - 2025 YAGEO