


MR-2

Aliases (USEZ2000000000)

KEMET, MR, Current, Round - Toroidal, Zero Phase Current, High Sensitivity, Compact



General Information	
Series	MR
Туре	Current
Style	Round - Toroidal
Description	Zero-Phase Current Transformers
Features	High Sensitivity, Compact
Lead	Cables
RoHS	Yes
REACH	Yes
Notes	Measurement Conditions: f=60Hz, R=300 Ohms, lo=22.5 mAmps

Click here for the 3D model.

Dimensions	
D	8.9mm MIN
Н	8.3mm MAX
D2	21.8mm MAX
D3	24.7mm MAX
D4	5mm NOM
LL	80mm +/-3mm

Packaging Specifications	
Packaging	Tray
Packaging Quantity	480
Typical Component Weight	5.9 g

Specifications	
Temperature Range	-20/+80°C
Voltage DC	8 mV MIN (Output)
Current	30 Amps
ESR	30 Ohms
Miscellaneous	Overinput characteristics (After DC5A input) = 10% MAX.

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 12/24/2025 © 2006 - 2025 YAGEO