



PEG130KL4390QL1

Aliases (PEG130KL4390Q)

Obsolete

PEG130, Aluminum, Aluminum Electrolytic, 3,900 uF, -10/+30%, 40 VDC, -40/+105°C



[Click here](#) for the 3D model.

General Information

Series	PEG130
Dielectric	Aluminum Electrolytic
Style	Axial
Description	Long Life Axial Aluminum Electrolytic
Features	Long Life
RoHS	Yes
Lead	Wire Leads
AEC-Q200	No
Halogen Free	Yes
Typical Component Weight	24 g
Notes	L1 is KEMETs recommendation for minimum distance between symmetrical Lead bend. Available only for Customer specific part numbers. Lead bend dimensions must be specified and confirmed per article. Dimensions D And L Include Sleeving.
Shelf Life	520 Weeks

Dimensions

D	20mm +/-0.5mm	Capacitance	3,900 uF
L	45mm +/-1mm	Tolerance	-10/+30%
L1	52mm MIN	Voltage DC	40 VDC
LL	40mm +/-2mm	Temperature Range	-40/+105°C
F	1mm +/-0.03mm	Rated Temperature	105°C

Packaging Specifications

Sleeving	Yes	ESR	33 mOhms (100Hz 20C), 19 mOhms (100kHz 20C), 11.3 mOhms (5-100kHz 105C)
Packaging	Bulk, Bag	Ripple Current	2.18 Amps (100Hz 105C), 12.3 Amps (5kHz 60C), 10 Amps (5kHz 80C), 5.5 Amps (5kHz 100C), 3.6 Amps (>=5kHz 105C)

Specifications

Leakage Current	472 uA (5min 20°C)
-----------------	--------------------

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.