


## PHE841ER712OKR06L2

Aliases (F841RK125K330C, PHE841ER712OKR02R06L2)

Not for New Design

PHE841/F841, Film, Metallized Polypropylene, Safety, 1.2 uF, 10%, 1,000 VDC, 330 VAC (X1), 100°C, 37.5 mm



Click [here](#) for the 3D model.

### General Information

Series	PHE841/F841
Dielectric	Metallized Polypropylene
Style	Radial
Features	EMI Safety
RoHS	Yes
Termination	Tinned Wire
Lead	Wire Leads
Safety Class	X1
Qualifications	ENEC, UL, cUL
Typical Component Weight	23.7 g

### Dimensions

L	41mm -0.7mm
H	32mm -0.7mm
T	16.5mm -0.7mm
S	37.5mm +/-0.4mm
LL	6mm NOM
F	1mm +/-0.05mm

### Packaging Specifications

Packaging	Tray
Packaging Quantity	105

### Specifications

Capacitance	1.2 uF
Tolerance	10%
Voltage DC	1000 VDC
Voltage AC	330 VAC (X1)
Temperature Range	-40/+100°C
Rated Temperature	100°C
Dissipation Factor	0.1% 1kHz, 0.8% 10kHz
Insulation Resistance	8.3333 GOhms
Max dV/dt	100 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.