



Click [here](#) for the 3D model.

### Dimensions

|    |                  |
|----|------------------|
| L  | 18mm +0.3/-0.5mm |
| H  | 12mm +0.1/-0.5mm |
| T  | 6mm +0.2/-0.5mm  |
| S  | 15mm +/-0.4mm    |
| LL | 30mm +5mm        |
| F  | 0.6mm +/-0.05mm  |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 900       |

### General Information

|                          |  |
|--------------------------|--|
| Series                   | R71  |
| Dielectric               | Metallized Polypropylene                       |
| Style                    | Radial   |
| Features                 | PFC and Pulse                                  |
| RoHS                     | Yes  |
| Lead                     | Wire Leads                                     |
| AEC-Q200                 | No   |
| Typical Component Weight | 1.931 g  |
| Miscellaneous            | Above 105C DC And AC Voltage Derating Is 4%/C. |

### Specifications

|                       |  |
|-----------------------|--|
| Capacitance           | 0.22 uF                                |
| Capacitance Tolerance | 10%                                    |
| Voltage DC            | 520 VDC                                |
| Voltage AC            | 250 VAC                                |
| Temperature Range     | -40/+110°C                             |
| Rated Temperature     | 105°C                                  |
| Dissipation Factor    | 0.1% 25C                               |
| Insulation Resistance | 100 GOhms                              |
| Max dV/dt             | 200 V/us                               |
| ESR                   | 253.2 mOhms (100kHz)                   |
| Ripple Current        | 0.81 Amps (100kHz 85C), 44 Amps (Peak) |
| Inductance            | 10 nH                                  |