

RM4A(03)-90X70T0800

Aliases (UFSRM4030KT080) EMI Suppression, KEMET, RM4A, Sheet, RFID

Т

	W
L	

General Information			
Series	RM4A		
Style	Sheet		
Description	Flex Suppressor Magnetic Sheet For RFID		
Features	High Magnetic Permeability Type, Low Magnetic Loss Type		
RoHS	Yes		
Environment	RoHS Compliant, Halogen Free, PVC Free, Lead Free, Red Phosphorus Free		

90x70mm
90mm NOM
70mm NOM
0.3mm NOM

Specifications		
Temperature Range	-40/+85°C	
Permeability	50 u At 13.56MHz	
Effective Frequency	13.56 MHz and below	
Specific Gravity	3.6 TYP	
Surface Resistivity	10 MOhm/sq. TYP	

Packaging Specifications

Typical Component Weight

7.06 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.