


## SSR10V-13097

Aliases (UALR10V1309700) Common Mode Chokes - Power, KEMET, SSR10V/H, Through-Hole Bobbin, Common Mode, 9,700 uH



| General Information |   |
|---------------------|---|
| Series              | SSR10V/H  |
| Style               | Through-Hole Bobbin   |
| Features            | Small Standard Common Mode,<br>High Permeability, Compact<br>Size, Low Profile, Light Weight,<br>High Impedance, Strong<br>Inductance |
| RoHS                | Yes   |
| Miscellaneous       | 55 (K) Temperature Rise Max.  |
| Core                | Mn-Zn Ferrite   |

Click here for the 3D model.

| Dimensions |                |
|------------|----------------|
| L          | 23.5mm MAX     |
| т          | 13mm MAX       |
| Н          | 21mm MAX       |
| LL         | 3.5mm +/-0.5mm |
| S          | 13mm +/-0.5mm  |
| S1         | 10mm +/-0.5mm  |
| Wire Size  | 0.37mm         |
| F          | 0.7mm NOM      |
|            |                |

| Specifications    |            |
|-------------------|------------|
| Voltage AC        | 250 VAC    |
| Inductance        | 9.7 mH     |
| Rated Current     | 1.3 A      |
| Temperature Range | -40/+120°C |
| DC Resistance     | 0.27 Ohms  |

## Packaging Specifications

| Packaging                | Tray |  |
|--------------------------|------|--|
| Packaging Quantity       | 600  |  |
| Typical Component Weight | 9 g  |  |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.