


**BOTTOM VIEW**



**CATHODE (-) END VIEW**



**SIDE VIEW**

Click [here](#) for the 3D model.

**General Information**

|                          |  |
|--------------------------|--|
| Series                   | T555                                     |
| Dielectric               | Polymer Tantalum                         |
| Style                    | SMD Chip                                 |
| RoHS                     | No                                       |
| SCIP Number              | 43449f08-bd3e-4b72-a04c-6c<br>a7dd4144ff |
| Termination              | Tin                                      |
| AEC-Q200                 | No                                       |
| Typical Component Weight | 5.54 g                                   |
| Shelf Life               | 156 Weeks                                |

**Dimensions**

|   |                 |
|---|-----------------|
| L | 24.5mm +/-0.5mm |
| W | 8.5mm +/-0.5mm  |
| H | 9.1mm +/-0.5mm  |
| S | 3mm +/-0.3mm    |
| F | 4.2mm +/-0.5mm  |

**Packaging Specifications**

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Box |
| Packaging Quantity | 100       |

**Specifications**

|                         |  |
|-------------------------|--|
| Capacitance             | 390 uF   |
| Tolerance               | 20%  |
| Voltage DC              | 15 VDC, 11.7 VDC (105°C), 17.25 VDC (85°C)                                 |
| Temperature Range       | -55/+105°C   |
| Rated Temperature       | 85°C   |
| Life                    | 2000 Hrs   |
| Dissipation Factor      | 5% (120Hz 25C)   |
| Failure Rate            | N/A  |
| ESR                     | 90 mOhm (100kHz 25C)   |
| Ripple Current          | 1750 mAmps (40kHz 85C)   |
| Leakage Current         | 43.9 uA (5min 25°C)  |
| Testing and Reliability | 25C +/-5C, 10 cycles, after constant voltage conditioning (KEMET standard) |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.