

USEQFSEA22L180

Aliases (USEQFSEA22L180)

General Information

Series


Type

Not for New Design

KEMET, QFS, Flame Detection, SMD, Infrared, Small SMD Package, 12C Communication Compatible

QFS

Flame Detection



| \$ 660 \$ 600 \$ 100 \$ | Style | SMD |
|--|----------------|--|
| | Description | 12C |
| | Features | Small SMD Package, 12C Communication Compatible |
| 91 650 or 00.90 | RoHS | With Exemptions |
| s 050 —— | REACH | SVHC (PZT - CAS 12626-81-2) |
| 0.550 1.370 1.55 Madmum | SCIP Number | f8c5f819-a3bd-41c4-887e-bd5 dcb8c5edf |
| | Qualifications | REACH |
| Click here for the 3D model. | MSL | 3 |
| | | |
| Dimensions | Specifications | |

| Dimensions | |
|--------------------------|------------|
| L | 5.65mm NOM |
| W | 3.7mm NOM |
| Т | 1.55mm MAX |
| | |
| Packaging Specifications | |

| Packaging Specifications | |
|--------------------------|------------|
| Packaging | T&R, 178mm |
| Packaging Quantity | 800 |
| Typical Component Weight | 70 mg |

| Specifications | |
|----------------------|--|
| Temperature Range | -40/+85°C |
| Power Supply Voltage | 1.75 - 3.6 V |
| Current | 1 - 23 uA (Supply Current, Typical) |
| Miscellaneous | Sensor Type: Single. |
| Field of View | 90 degrees |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 09/17/2025 © 2006 - 2025 YAGEO