




KEMET, VP, Varistors, Commercial Grade, 200 V, 150 VAC, 395 V, 10 A, 1.2 kA, 18.5 J



General Information	
Supplier	KEMET
Series	VP
Туре	Varistors
Style	SMD Molded
Description	Surface Mount Varistors
Features	Plastic Encapsulated
Termination	Nickel Tin
RoHS	With Exemptions
AEC-Q200	No

Click here for the 3D model.

10mm +/-0.5mm
8mm +/-0.4mm
4.7mm +/-0.3mm
3mm +/-0.3mm
1.5mm +/-0.3mm
2.3mm +/-0.3mm
4032 / 10281

Packaging Specifications	
Packaging	T&R
Packaging Quantity	1000

Specifications	
Voltage DC	200 VDC (25C)
Voltage AC	150 VAC
Temperature Range	-40/+85°C
Storage Temperature Range	-40/+125°C
Varistor Voltage	240 VDC at 1 mA
Clamping Voltage	395 V
Clamping Current	10 A (8/20 us MAX)
Surge Current	1200 A (8/20 us MAX)
Energy	18.5 J (10/1000 us MAX)
Power	0.25 W (MAX)
Capacitance	280 pF (1kHz)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 12/27/2025 © 2006 - 2025 YAGEO