




ARR Indust X7R HT200C, Ceramic, 0.1 uF, 10%, 25 VDC, X7R, Commercial, High Temperature, 5.08 mm



General Information	
Series	ARR Indust X7R HT200C
Style	Radial
Description	Commercial, High Temperature
Features	Commercial
RoHS	No
Prop 65	WARNING: Cancer and reproductive harm - https://www.p65warnings.ca.gov /
SCIP Number	f2ec9c71-d741-45f9-8d01-f6de 6baf235a
Termination	Gold
Lead	Wire Leads
Testing and Reliability	Standard
AEC-Q200	No

L 7.62mm MAX W 7.62mm MAX T 2.54mm MAX S 5.08mm +/-0.38mm LL 3.175mm MIN F 0.508mm +/-0.05mm	Dimensions	
T 2.54mm MAX S 5.08mm +/-0.38mm LL 3.175mm MIN	L	7.62mm MAX
S 5.08mm +/-0.38mm LL 3.175mm MIN	W	7.62mm MAX
LL 3.175mm MIN	Т	2.54mm MAX
	S	5.08mm +/-0.38mm
F 0.508mm +/-0.05mm	LL	3.175mm MIN
	F	0.508mm +/-0.05mm

Specifications	
Capacitance	0.1 uF
Tolerance	10%
Voltage DC	25 VDC
Temperature Range	-55/+200°C
Temp. Coefficient	X7R
Dissipation Factor	2.5% 1 kHz 1.0 Vrms
Insulation Resistance	10 GOhms

Packaging Specifications	
Packaging	Bulk, Bag

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 05/02/2025 © 2006 - 2025 YAGEO