


## C0603T473K1RCLTU

Aliases (C0603T473K1RCL7867) SMD COTS X7R, Ceramic, 0.047 uF, 10%, 100 VDC, X7R, SMD, MLCC, COTS, Temperature Stable, Class II, 0603, 0.5 mm



| General Information      |   |
|--------------------------|---|
| Series                   | SMD COTS X7R  |
| Style                    | SMD Chip  |
| Description              | SMD, MLCC, COTS,<br>Temperature Stable, Class II  |
| Features                 | Temperature Stable, Class II  |
| RoHS                     | No  |
| Prop 65                  | WARNING: Cancer and reproductive harm - https://www.p65warnings.ca.gov /                                      |
| SCIP Number              | 2d771165-5336-48a3-96fa-366<br>3929fd828  |
| Termination              | Lead (SnPb)   |
| Marking                  | No  |
| Failure Rate             | Testing per MIL-PRF-55681 PDA<br>8%, DPA per EIA-469, Humidity<br>per MIL-STD-202, Method 103,<br>Condition A |
| AEC-Q200                 | No  |
| Typical Component Weight | 4.8 mg  |
| Shelf Life               | 78 Weeks  |
| MSL                      | 1   |

| Dimensions |                  |
|------------|------------------|
| Chip Size  | 0603             |
| L          | 1.6mm +/-0.15mm  |
| W          | 0.8mm +/-0.15mm  |
| Т          | 0.8mm +/-0.07mm  |
| S          | 0.5mm MIN        |
| В          | 0.35mm +/-0.15mm |

| Packaging Specifications |                        |
|--------------------------|------------------------|
| Packaging                | T&R, 180mm, Paper Tape |
| Packaging Quantity       | 4000                   |

| Specifications   |  |
|--|--|
| Capacitance  | 0.047 uF   |
| Measurement Condition  | 1 kHz 1.0Vrms                                      |
| Tolerance  | 10%  |
| Voltage DC   | 100 VDC  |
| Dielectric Withstanding Voltage  | 250 VDC  |
| Temperature Range  | -55/+125°C   |
| Temp. Coefficient  | X7R  |
| Capacitance Change with<br>Reference to +25°C and 0 VDC<br>Applied (TCC) | 15%, 1kHz 1.0Vrms                                  |
| Dissipation Factor   | 2.5% 1 kHz 1.0Vrms                                 |
| Aging Rate   | 3% Loss/Decade Hour: Referee<br>Time is 1000 Hours |
| Insulation Resistance  | 10 GOhms   |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 10/29/2025 © 2006 - 2025 YAGEO