


## **C0805A330F2GAH** GR900 SMD Space BP, Ceramic, 33 pF, 1%, 200 VDC, BP, N/A, 0805

**General Information** 



Series	GR900 SMD Space BP
Style	SMD Chip
RoHS	No
Prop 65	WARNING: Cancer and reproductive harm - https://www.p65warnings.ca.gov /
SCIP Number	2a1e1a41-ed35-45dd-8d0d-907 fc06efdab
Termination	Lead (SnPb)
Failure Rate	N/A
Testing and Reliability	GR900 CSAM A
AEC-Q200	No
Shelf Life	78 Weeks
MSL	1

0805
2.03mm +/-0.38mm
1.27mm +/-0.38mm
1.4mm MAX
0.51mm +/-0.25mm

Specifications	
Capacitance	33 pF
Tolerance	1%
Voltage DC	200 VDC
Temperature Range	-55/+125°C
Temp. Coefficient	BP

## **Packaging Specifications**

Packaging

Bulk, Bag

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.