

General Information

Specifications


Capacitance Tolerance

Voltage DC

Temperature Range Temp. Coefficient

Series

Style



RoHS No Prop 65 WARNING: Cancer and reproductive harm https://www.p65warnings.ca.gov 2a1e1a41-ed35-45dd-8d0d-907 SCIP Number fc06efdab Termination Lead (SnPb) Failure Rate N/A Testing and Reliability GR900 CSAM A AEC-Q200 No Shelf Life 78 Weeks MSL 1

0.01 uF

-55/+125°C

10% 100 VDC

ΒX

GR900 SMD Space BX

SMD Chip

Dimensions	
Chip Size	1206
L	3.07mm +/-0.38mm
W	1.52mm +/-0.38mm
т	1.6mm MAX
В	0.51mm +/-0.25mm

Packaging Specifications	

Packaging

Bulk, Bag

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and
we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the
requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us
with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.