

C1812C183JCRACTU

Aliases (C1812C183JCRAC7800) SMD Comm X7R HV, Ceramic, 0.018 uF, 5%, 500 VDC, X7R, SMD, MLCC, High Voltage, Temperature Stable, 1812, 2.3 mm



Click here for the 3D model.

	General Information	
	Series	SMD Comm X7R HV
	Style	SMD Chip
	Description	SMD, MLCC, High Voltage, Temperature Stable
	Features	High Voltage
	RoHS	Yes
	Termination	Tin
	Marking	No
	AEC-Q200	No
	Typical Component Weight	95 mg
	Shelf Life	78 Weeks
	MSL	1

Specifications	
Capacitance	0.018 uF
Measurement Condition	1 kHz 1.0Vrms
Tolerance	5%
Voltage DC	500 VDC
Dielectric Withstanding Voltage	750 VDC
Temperature Range	-55/+125°C
Temp. Coefficient	X7R
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	15%, 1kHz 1.0Vrms
Dissipation Factor	2.5%1kHz1.0Vrms
Aging Rate	3% Loss/Decade Hour: Referee Time is 1000 Hours
Insulation Resistance	55.5556 GOhms

 Dimensions

 Chip Size
 1812

 L
 4.5mm +/-0.3mm

 W
 3.2mm +/-0.3mm

 T
 1mm +/-0.10mm

 S
 2.3mm MIN

 B
 0.6mm +/-0.35mm

Packaging Specifications

Packaging	T&R, 180mm, Plastic Tape
Packaging Quantity	1000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.