
C2225A105K5XAG

GR900 SMD Space BX, Ceramic, 1 uF, 10%, 50 VDC, BX, N/A, 2225





Click here	for the	3D	model
------------	---------	----	-------

General Information	
	ODOGG GMD G DV
Series	GR900 SMD Space BX
Style	SMD Chip
RoHS	Yes
Termination	Gold
Failure Rate	N/A
Testing and Reliability	GR900 CSAM A
AEC-Q200	No
Shelf Life	78 Weeks
MSL	1

Dimensions	
Chip Size	2225
L	5.59mm +/-0.38mm
W	6.35mm +/-0.38mm
Т	2.03mm MAX
В	0.51mm +/-0.25mm

Packaging Specifications		
Packaging	Bulk, Bag	

Specifications	
Capacitance	1uF
Tolerance	10%
Voltage DC	50 VDC
Temperature Range	-55/+125°C
Temp Coefficient	BX

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 08/03/2025 © 2006 - 2025 YAGEO