


## C315C222K1R5TA91707303

Aliases (C315C222K1R5TA9170TR)
GoldMay 300 Auto X7R Ceramic 2 200 pF 10% 100 VDC

GoldMax 300 Auto X7R, Ceramic, 2,200 pF, 10%, 100 VDC, X7R, GoldMax, Automotive Grade, 2.54 mm



Click here for the 3D model.

Click here for the 3D model.		
Dimensions		
L	3.81mm MAX	
Н	3.14mm MAX	
Т	2.54mm MAX	
S	2.54mm +/-0.78mm	
НО	18mm MIN	
F	0.51mm +0.1/-0.025mm	

Packaging Specifications	
Packaging	T&R, 305mm
Packaging Quantity	2500

General Information	
Series	GoldMax 300 Auto X7R
Style	Radial
Description	GoldMax, Automotive Grade
Features	Automotive Grade
RoHS	Yes
Termination	Tin
Lead	Wire Leads
Failure Rate	N/A
Qualifications	AEC-Q200
AEC-Q200	Yes
Halogen Free	Yes

Specifications	
Capacitance	2,200 pF
Measurement Condition	1 kHz 1.0Vrms
Tolerance	10%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	250 VDC
Temperature Range	-55/+125°C
Temp. Coefficient	X7R
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	0.15, 1kHz 1.0Vrms
Dissipation Factor	2.5%1kHz1.0Vrms
Aging Rate	3% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 11/05/2025 © 2006 - 2025 YAGEO