




GoldMax 300 Comm X7R, Ceramic, 1,000 pF, 20%, 100 VDC, X7R, GoldMax, Commercial Standard, 2.54 mm



Click	here	for	the	3D	model.
CIICK	11515	101			mou c i.

General Information			
Series	GoldMax 300 Comm X7R		
Style	Radial		
Description	GoldMax, Commercial Standard		
RoHS	Yes		
Termination	Tin		
Lead	Crimped Out		
Failure Rate	N/A		
AEC-Q200	No		
Halogen Free	Yes		

Dimensions	
L	3.81mm MAX
Н	5.84mm MAX
Т	2.54mm MAX
S	2.54mm +/-0.78mm
НО	16mm +/-0.5mm
F	0.51mm +0.1/-0.025mm
Е	5.08mm NOM

Packaging Specifications		
Packaging	T&R, 305mm	
Packaging Quantity	2500	

Specifications	
Capacitance	1,000 pF
Measurement Condition	1 kHz 1.0Vrms
Tolerance	20%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	250 VDC
Temperature Range	-55/+125°C
Temp. Coefficient	X7R
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	0.15, 1kHz 1.0Vrms
Dissipation Factor	2.5% 1 kHz 1.0Vrms
Aging Rate	3% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 11/04/2025 © 2006 - 2025 YAGEO