


General Information

Series	AxiMax 400 Comm X7R
Description	AxiMax, Commercial Standard
RoHS	Yes
Termination	Tin
Lead	Wire Leads
Failure Rate	N/A
Halogen Free	Yes

Click [here](#) for the 3D model.

Dimensions

D	3.05mm MAX	Capacitance	0.056 uF
L	4.32mm MAX	Measurement Condition	1 kHz 1.0Vrms
LL	25.4mm MIN	Tolerance	10%
F	0.51mm +0.025/-0.076mm	Voltage DC	50 VDC

Packaging Specifications

Packaging	Bulk, Bag	Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	0.15, 1kHz 1.0Vrms
Packaging Quantity	200	Dissipation Factor	2.5% 1kHz 1.0Vrms
		Aging Rate	3% Loss/Decade Hour: Referee Time is 1000 Hours
		Insulation Resistance	17.86 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.