



## CA064X220K5GACAUTO

Not for New Design

Array Auto COG Flex, Ceramic, 22 pF, 10%, 50 VDC, COG, SMD, MLCC, Array, Flex Termination, Automotive Grade, 0612  $\,$ 





Click here for the 3D model.

Dimensions	
L	1.6mm +/-0.2mm
W	3.2mm +/-0.2mm
Т	0.8mm +/-0.10mm

Packaging Specifications		
Packaging	T&R, 180mm, Paper Tape	
Packaging Quantity	4000	

General Information		
Series	Array Auto COG Flex	
Style	SMD Array	
Description	SMD, MLCC, Array, Flex Termination, Automotive Grade	
Features	Automotive Grade	
RoHS	Yes	
Termination	Flexible Termination	
Qualifications	AEC-Q200	
AEC-Q200	Yes	
Chip Size	0612	
MSL	1	

Specifications	
Capacitance	22 pF
Capacitance Tolerance	10%
Voltage DC	50 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	COG
Dissipation Factor	0.1% 1 MHz 1.0Vrms
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.