

## CGP1C330KGSDCAWL50

CGP DISC Comm HV, Ceramic, 33 pF, 10%, 2,000 VDC, SL, 10 mm



Packaging Specifications

Packaging Quantity

Packaging



The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

General Information	
Series	CGP DISC Comm HV
Style	Radial Disc
RoHS	Yes
Termination	Tin
Lead	Crimped Out
Failure Rate	N/A
AEC-Q200	No
Halogen Free	Yes

33 pF

10%

SL

2000 VDC

-25/+85°C

Click here for the 3D model.

Dimensions	
D	6mm MAX
т	5mm MAX
S	10mm NOM
LL	5mm +/-1mm
F	0.6mm +/-0.1mm
V	1.7mm +/-0.5mm

Bulk

0.6mm +/-0.1mm	Temp. Coefficient
1.7mm +/-0.5mm	

Specifications Capacitance

Tolerance

Voltage DC

**Temperature Range** 

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.