CGP1C471MGYDDA7301

CGP DISC Comm HV, Ceramic, 470 pF, 20%, 2,000 VDC, Y5P, 10 mm





General Information	
Series	CGP DISC Comm HV
Style	Radial Disc
RoHS	Yes
Termination	Tin
Lead	Snap-In Crimp
Failure Rate	N/A
AEC-Q200	No
Halogen Free	Yes

Click here for the 3D model.

D 7.5mm MAX T 5mm MAX S 10mm NOM LL 16mm +2/-0mm	Dimensions	
S 10mm NOM	D	7.5mm MAX
	Т	5mm MAX
LL 16mm +2/-0mm	S	10mm NOM
	LL	16mm +2/-0mm
F 0.6mm +/-0.1mm	F	0.6mm +/-0.1mm
V 1.7mm +/-0.5mm	V	1.7mm +/-0.5mm

Packaging Specifications	
Packaging	T&R
Packaging Quantity	2000

Specifications	
Capacitance	470 pF
Tolerance	20%
Voltage DC	2000 VDC
Temperature Range	-30/+85°C
Temp. Coefficient	Y5P

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 09/12/2025 © 2006 - 2025 YAGEO