

## CGP1C472MLWDDAWL25

CGP DISC Comm HV, Ceramic, 4,700 pF, 20%, 8,000 VDC, Y5U, 10 mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

General Information	
Series	CGP DISC Comm HV
Style	Radial Disc
RoHS	Yes
Termination	Tin
Lead	Snap-In Crimp
Failure Rate	N/A
AEC-Q200	No
Halogen Free	Yes

Click here for the 3D model.

D       21mm MAX         T       9mm MAX         S       10mm NOM         LL       25mm MIN         F       0.8mm +/-0.1mm         V       4.3mm +/-0.5mm	Dimensions	
S         10mm NOM           LL         25mm MIN           F         0.8mm +/-0.1mm	D	21mm MAX
LL         25mm MIN           F         0.8mm +/-0.1mm	Т	9mm MAX
F 0.8mm +/-0.1mm	S	10mm NOM
0.01111 / 0.11111	LL	25mm MIN
V 4.3mm +/-0.5mm	F	0.8mm +/-0.1mm
	V	4.3mm +/-0.5mm

200

Specifications	
Capacitance	4,700 pF
Tolerance	20%
Voltage DC	8000 VDC
Temperature Range	-30/+85°C
Temp. Coefficient	Y5U

## Packaging Specifications Packaging Bulk

Packaging Quantity

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.