

CGP1C689JLSDAAWL35









The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

General Information CGP DISC Comm HV Series Radial Disc Style RoHS Yes Termination Tin Lead Wire Leads Failure Rate N/A AEC-Q200 No Halogen Free Yes

Click here for the 3D model.

Dimensions	
D	8.5mm MAX
Т	8mm MAX
S	10mm NOM
LL	3.5mm +/-1mm
F	0.8mm +/-0.1mm
V	4.3mm +/-0.5mm

Packaging Specifications	
Packaging	Bulk
Packaging Quantity	500

Specifications	
Capacitance	6.8 pF
Tolerance	5%
Voltage DC	8000 VDC
Temperature Range	-25/+85°C
Temp. Coefficient	SL

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 07/09/2025 © 2006 - 2025 YAGEO