


CGP2C121JGSDCA7317 CGP DISC Comm HV, Ceramic, 120 pF, 5%, 2,000 VDC, SL, 12.5 mm



The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

Specifications Capacitance

Tolerance

Voltage DC

Temperature Range

General Information	
Series	CGP DISC Comm HV
Style	Radial Disc
RoHS	Yes
Termination	Tin
Lead	Crimped Out
Failure Rate	N/A
AEC-Q200	No
Halogen Free	Yes

120 pF

2000 VDC

-25/+85°C

5%

SL

Click here for the 3D model.

Dimensions	
D	10mm MAX
т	5mm MAX
S	12.5mm NOM
LL	16mm +2/-0mm
F	0.6mm +/-0.1mm
V	1.7mm +/-0.5mm

1500

	0.6mm +/-0.1mm	Temp. Coefficient
	1.7mm +/-0.5mm	
pecifications		
	Ammo	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Packaging Sp Packaging

Packaging Quantity