CGP2C130KKSDDA7301

CGP DISC Comm HV, Ceramic, 13 pF, 10%, 6,000 VDC, SL, 12.5 mm





General Information	
Series	CGP DISC Comm HV
Style	Radial Disc
RoHS	Yes
Termination	Tin
Lead	Snap-In Crimp
Failure Rate	N/A
AEC-Q200	No
Halogen Free	Yes

Click here for the 3D model.

D 7.5mm MAX T 6mm MAX S 12.5mm NOM LL 16mm +2/-0mm F 0.6mm +/-0.1mm V 2.7mm +/-0.5mm	Dimensions	
S 12.5mm NOM LL 16mm +2/-0mm F 0.6mm +/-0.1mm	D	7.5mm MAX
LL 16mm +2/-0mm F 0.6mm +/-0.1mm	Т	6mm MAX
F 0.6mm +/-0.1mm	S	12.5mm NOM
0.011111 / 0.111111	LL	16mm +2/-0mm
V 2.7mm +/-0.5mm	F	0.6mm +/-0.1mm
•	V	2.7mm +/-0.5mm

Packaging Specifications	
Packaging	T&R
Packaging Quantity	1000

Specifications	
Capacitance	13 pF
Tolerance	10%
Voltage DC	6000 VDC
Temperature Range	-25/+85°C
Temp. Coefficient	SL

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 06/06/2025 © 2006 - 2025 YAGEO