

CGP2C130KUSDDA7301

CGP DISC Comm HV, Ceramic, 13 pF, 10%, 4,000 VDC, SL, 12.5 mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

| General Information | |
|---------------------|------------------|
| Series | CGP DISC Comm HV |
| Style | Radial Disc |
| RoHS | Yes |
| Termination | Tin |
| Lead | Snap-In Crimp |
| Failure Rate | N/A |
| AEC-Q200 | No |
| Halogen Free | Yes |

Click here for the 3D model.

| Dimensions | |
|------------|----------------|
| D | 6.5mm MAX |
| т | 5mm MAX |
| S | 12.5mm NOM |
| LL | 16mm +2/-0mm |
| F | 0.6mm +/-0.1mm |
| V | 2.1mm +/-0.5mm |

| Specifications | |
|-------------------|-----------|
| Capacitance | 13 pF |
| Tolerance | 10% |
| Voltage DC | 4000 VDC |
| Temperature Range | -25/+85°C |
| Temp. Coefficient | SL |

| Packaging Specifications | |
|--------------------------|------|
| Packaging | T&R |
| Packaging Quantity | 1000 |

| Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and |
|--|
| we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the |
| requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us |
| with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained. |