

## CGP2C152MNWDAAWL35

CGP DISC Comm HV, Ceramic, 1,500 pF, 20%, 10,000 VDC, Y5U, 12.5 mm



**Packaging Specifications** 

Packaging Quantity

Packaging



The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

General Information	
Series	CGP DISC Comm HV
Style	Radial Disc
RoHS	Yes
Termination	Tin
Lead	Wire Leads
Failure Rate	N/A
AEC-Q200	No
Halogen Free	Yes

1,500 pF 20%

10000 VDC

Click here for the 3D model.

Dimensions	
D	14.5mm MAX
т	10mm MAX
S	12.5mm NOM
LL	3.5mm +/-1mm
F	0.8mm +/-0.1mm
V	4.9mm +/-0.5mm

Bulk

3.5mm +/-1mm	Temperature Range	-30/+85°C
0.8mm +/-0.1mm	Temp. Coefficient	Y5U
4.9mm +/-0.5mm		

Specifications Capacitance

Tolerance Voltage DC

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.