

CGP2C330KNSDAAWL50

CGP DISC Comm HV, Ceramic, 33 pF, 10%, 10,000 VDC, SL, 12.5 mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

General Information	
Series	CGP DISC Comm HV
Style	Radial Disc
RoHS	Yes
Termination	Tin
Lead	Wire Leads
Failure Rate	N/A
AEC-Q200	No
Halogen Free	Yes

33 pF

10000 VDC

10%

Click here for the 3D model.

Dimensions	
D	10mm MAX
т	8mm MAX
S	12.5mm NOM
LL	5mm +/-1mm
F	0.8mm +/-0.1mm
V	4.9mm +/-0.5mm

	•	
ı	Temperature Range	-25/+85°C
lmm	Temp. Coefficient	SL
5mm		

Specifications Capacitance

Tolerance

Voltage DC

Packaging Specifications	
Packaging	Bulk
Packaging Quantity	500

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.