

CGP2C360KGSDAAWL25

CGP DISC Comm HV, Ceramic, 36 pF, 10%, 2,000 VDC, SL, 12.5 mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

| General Information | |
|---------------------|------------------|
| Series | CGP DISC Comm HV |
| Style | Radial Disc |
| RoHS | Yes |
| Termination | Tin |
| Lead | Wire Leads |
| Failure Rate | N/A |
| AEC-Q200 | No |
| Halogen Free | Yes |

Click here for the 3D model.

| Dimensions | |
|------------|----------------|
| D | 6mm MAX |
| т | 5mm MAX |
| S | 12.5mm NOM |
| LL | 25mm MIN |
| F | 0.6mm +/-0.1mm |
| V | 1.7mm +/-0.5mm |

200

| F | 0.6mm +/-0.1mm | Temp. Coefficient |
|--------------------------|----------------|-------------------|
| V | 1.7mm +/-0.5mm | |
| | | |
| Packaging Specifications | | |
| Packaging | Bulk | |

Specifications Capacitance 36 pF Tolerance 10% Voltage DC 2000 VDC -25/+85°C **Temperature Range** Temp. Coefficient SL

| Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and |
|--|
| we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the |
| requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us |
| with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained. |

Packaging Quantity