

CGP2C680KHSDAAWL25

CGP DISC Comm HV, Ceramic, 68 pF, 10%, 3,000 VDC, SL, 12.5 mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

General Information		
Series	CGP DISC Comm HV	
Style	Radial Disc	
RoHS	Yes	
Termination	Tin	
Lead	Wire Leads	
Failure Rate	N/A	
AEC-Q200	No	
Halogen Free	Yes	

68 pF

3000 VDC -25/+85°C

10%

SL

Click here for the 3D model.

Dimensions	
D	8.5mm MAX
т	5mm MAX
S	12.5mm NOM
LL	25mm MIN
F	0.6mm +/-0.1mm
V	2.1mm +/-0.5mm

200

F	0.6mm +/-0.1mm	Temp. Coefficient
V	2.1mm +/-0.5mm	
Packaging Specifications		
Packaging	Bulk	

Specifications Capacitance

Tolerance

Voltage DC

Temperature Range

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Packaging Quantity